

# MARINTEK FACT SHEET

## ShipX - Station Keeping




### A Program for Predicting Station Keeping Performance of Ships

MARINTEK has developed a program for numerical calculation of station keeping performance of ships. This program is integrated in the hydrodynamic workbench ShipX.

The motivation for developing this software was to enable the ShipX workbench environment to provide the user with station keeping prediction capabilities. In addition, existing programs were complicated to use requiring manual editing of input files, limiting user settings with respect to prediction options and lacking features required by our customers. In the development of ShipX station keeping software, a fast-to-use, easy-to-learn user interface has been one of the main focuses.

The station keeping software is integrated as an application in ShipX, and has the same intuitive, easy-to-use user interface as the rest of ShipX. Running the calculations takes from a few seconds up to a few minutes, depending on the speed of the computer, the number of environmental headings calculated for and the calculation method used. As




soon as the calculations are finished, reports and plots are available directly from ShipX. Reports and plots can easily be exported to Microsoft Word for quick and easy report generating.

### Numerical Methods

The station keeping software has several calculation modes (see Figure 2). In force generator load mode the user define the environmental effects. The calculated result is the load on each force generator (see Figure 3). In capability study mode the user defines what environmental forces to include, and the program will iterate the magnitude of the forces to find the maximum withstandable environmental force for each heading (see Figure 1). The station keeping program also supports both IMCA [1] and DNV [2] calculation methods.

A number of generic force generators are implemented in the program, including rudder and propeller units. The user can implement their own force generators through an open programming interface (using either Java or Fortran).

The allocation routine implemented uses quadratic programming with minimum thrust optimization. The allocation



Please turn the page

routine handles thrust saturation on all force generators. The users can implement their own allocation methods through an open programming interface (using Java).

The environmental forces are based on force coefficients. Databases for wind-, current- and wave drift coefficients for a range of ships are included. Additional coefficients can be imported from open file formats, literature and other software.




Figure 2. Calculation structure




Figure 3. Force generator load plot

References:

- [1] IMCA - "Specification for DP Capability Plots" IMCA M 140 Rev 1, 2000
- [2] Det Norske Veritas - "Capability Plots and Environmental Regularity Numbers" - Pt.6 Ch.26 Sec.7 - Page 23 Rules for Ships, July 2010