

Centre for intelligent electricity distribution - to empower the future Smart Grid

Application of New Sensors and Controllers for Distribution Grid Operation

Romina MUKA

Department of Information Security and Communication Technology, NTNU

Challenge and objectives

- Real time operation and decision support; increasing need for pervasive monitoring, self-healing and automation.
- Increased decentralization due to DER with new flexibility options; changes in the Distribution Grid (DG) (prosumers, peak loads).
- Current communication solutions used by DSOs not prepared for real-time and reliability requirements; maintaining grid health and stability.

Research tasks

Significant results

Preliminary results from simulation studies show how the probability of information inconsistencies change under different conditions.

Conclusions

- Inconsistencies between the state of the grid reported in the Distribution Management System (DMS) and the real state of the grid is a relevant problem.
- As the DG becomes more dependent on
- Study system services of grid operations in the future DG; and investigate how the Security of Supply is improved by adding more sensors/controllers to enable e.g., advanced protection and self-healing, improve voltage control, reduce fault localization.
- Develop strategies for deployment of sensors and controllers in the DG, taking communication network constraints into account.
- Identify and analyze interdependencies and reliability in the combined ICT and Power Systems.

Approach

- Modelling with Stochastic Activity Networks. Software

computers and automation, it will become more important to understand mechanisms behind these the inconsistencies in order to assess the reliability of future power systems.

- Smart grid reliability will be improved by integrating the information collected from sensors and controllers into DMS and proposing a new algorithm for sensors' placement.

Illustration



bugs, communication failures, wrong sensor readings and mechanical malfunction of disconnectors are included to assess the probability of information inconsistencies in the monitoring.

Optimization Problem placement for of sensors/controllers in remotely controlled DG using Genetic Algorithm.

Surveillance and control system with distributed sensors and controllers (IEDs).

This work is funded by CINELDI - Centre for intelligent electricity distribution, an 8 year Research Centre under the FME-scheme (Centre for Environment-friendly Energy Research, 257626/E20). The authors gratefully acknowledge the financial support from the Research Council of Norway and the CINELDI partners.