

CONFLOWS

Using wind farm control on floating wind farms

Research project outline

R. Ruisi¹, E. Bossanyi¹, M. Bastankhah², J. Chapman³, R. B. Tommasini³, M. Ogbeifun³, G. Foster³, P. Fleming⁴

DeepWind 2022 conference

20 January 2022

Summary

1

Project outline

2

Benchmark: site characteristics and floating platform

3


Wake modelling & wind farm control (WFC)

4

Next steps & conclusions


CONFLOWS

CONtrol of FLoating wind farms using Wake Steering



Collaboration on:

- Meteorological conditions
- Turbine wake simulations
- Wake model development
- Optimal control strategies




Objectives:


- increase confidence in the modelling and use of wake steering
- identifying challenges and advantages of using wake steering on floating offshore wind farms
- analysing economic effects of wake steering on floating platforms (*accelerate LCoE reduction*)

Reference Site


- WRF simulations performed at multiple sites around the US coast
- Benchmark site picked: Vineyard, N-E coast
- WRF and Metocean data used to size platform




10m Wind Rose



150m Wind Rose




Wave Rose



| Variable | Mean | Max | Standard deviation |
|-----------------|------|------|--------------------|
| Hs | 1.8 | 11.7 | 1.0 |
| Tp | 7.9 | 20.9 | 1.9 |
| Tm01 | 6.7 | 14.3 | 1.2 |
| 100m Wind Speed | 9.2 | 39.6 | 4.6 |

The MPS PelaFlex platform



PelaFlex Platform Configuration

(Credit: Marine Power Systems)

- Top tension platform system for hosting wind turbine system
- Truss system of connected braces for wind turbine system support
- Taut leg moorings – anchor the platform to the seabed
- Platform can be sized for a wide range of wind turbines



PelaFlex platform, (Credit: Marine Power Systems)

The MPS PelaFlex platform: motion

Preliminary testing sea & wind conditions:

$$H_s = 8 \text{ m}$$

$$T_p = 14 \text{ s}$$

Depth = 100m




Wind speed = 8 m/s (constant profile – NPD Spectrum)

Wind and wave aligned with turbine axis

Hosted Wind Turbine: NREL 15 MW

Hub height: 145 m


Diameter: 240 m




| Orcaflex results | Mean |
|------------------|--------|
| Nacelle pitch | -0.3 ° |
| Nacelle surge | -3.7 m |

Engineering wake models

- Literature review on floating-turbine wakes
 - Wake dynamics, wake steering, atmospheric conditions
- Improve models: LES simulations, focusing on the effect of veer (and atm. stability) on normal and yawed operations.



Influence of atmospheric stability @ Reference site




stable → { *less mixing*
greater wake deficits


unstable → { *more mixing*
smaller wake deficits

Engineering wake models


- Importance of veer increases with increase in rotor size




WRF @
Reference site




- Veer affects curl-shaped wake when wake steering (impact on power and WFC effectiveness)



Optimisation & simulation process



LongSim



Waked wind characteristics of all turbines




Wake steering setpoints

Loads estimation (surrogate loads model)



OrcaFlex

To analyse Loads and Response to waked and yawed conditions



Conclusions & Next steps



- ✓ *International collaboration started (June 2021 – March 2023)*
- ✓ *WRF simulations finalised at multiple sites and final reference site chosen*
- ✓ *Metocean conditions assessed and floating platform being sized*
- ✓ *LES simulations with strong veer conditions performed*
- ✓ *Literature review on turbine wakes in floating wind farms carried out*



1. *Model veer effects on deflected wakes starting from LES simulations*
2. *Finalise design of floating system; test turbine controller prior to wake steering optimisation*
3. *Perform simulations on a reference turbine layout and optimise wake steering strategy*
4. *Above results fed into offshore platform simulations to capture loads and response in (waked) normal and yawed operational conditions*
5. *Assess advantages and disadvantages of using WFC in a floating wind farm, deducing impact on LCoE*

Acknowledgements



CL-Windcon

CL-Windcon project, funded by European Union's Horizon 2020 research and innovation programme under grant agreement no. 727477 (www.clwindcon.eu).



TotalControl

TotalControl project, funded by European Union's Horizon 2020 research and innovation programme under grant agreement no. 727680 (www.totalcontrolproject.eu).



FarmConnors

FarmConnors project, funded by European Union's Horizon 2020 research and innovation programme under grant agreement no. 857844 (www.windfarmcontrol.info).



The National Offshore Wind Research and Development Consortium, established in 2018, is a not-for-profit public-private partnership focused on advancing offshore wind technology in the United States through high impact research projects and cost-effective and responsible development to maximize economic benefits. Funding for the Consortium comes from the [U.S. Department of Energy](https://www.energy.gov/) and the [New York State Energy Research and Development Authority](https://www.nyserda.org/) (NYSERDA), with each providing \$20.5 million, as well as contributions from the Commonwealths of Virginia and Massachusetts and the States of Maryland and Maine, bringing total investment to approximately \$47 million. For more information, please visit nationaloffshorewind.org.

The authors of this presentation do not own the rights of some of the images here reproduced, which were used for explanation purposes only. All the original owners have been credited where possible.

Thanks for your attention!

Questions?



renzo.ruisi@dnv.com / ervin.bossanyi@dnv.com

www.dnv.com





(Extra slides) LongSim: surrogate loads model

Comparison to Bladed




Blade root bending moment: spectra and DEL's




(Extra slides) LongSim: WFC optimisation

Lillgrund offshore wind farm – Steady state optimisation
48 turbines, Siemens 2.3 MW, very close spacing



Optimisation with and without loads



Induction control vs wake steering

