

N₂-CO₂ co-injection field test at Ketzin pilot CO₂ storage site

Sebastian Fischer, Martin Zimmer, Alexandra Szizybalski, Christian Kujawa, Birgit Plessen, Axel Liebscher, Fabian Moeller, and the Ketzin Team

GFZ German Research Centre for Geosciences

Abstract

Between June 2008 and August 2013 67,271 t of high-purity CO_2 were injected into a saline aquifer of the Stuttgart Formation at Ketzin, Germany. Both R&D programs as well as the applied monitoring methods at the Ketzin site are amongst the most comprehensive worldwide. Hence, scientific investigations at Ketzin provide fundamental knowledge for geological CO_2 storage in saline aquifers and the site is recognized as a reference project for the investigation and realization of geological CO_2 storage in general.

In summer 2013, a four week N₂-CO₂ co-injection field test was conducted at the Ketzin site within the scope of the IMPACTS project. The IMPACTS project is granted under the Seventh Framework Program by the European Commission and intends to evaluate the chemical and physical effects of impurities within the CO₂ stream during capture, transport and storage of (impure) CO₂. Major objectives of the N₂-CO₂ co-injection field test were i) demonstrating the technical feasibility of a continuous CO₂-N₂ co-injection scenario, ii) monitoring pressure evolution at the wellhead and of the reservoir, iii) monitoring spreading and behavior of the CO₂-N₂ gas mixture in the reservoir, and iv) analyzing potential chromatographic effects within the reservoir. In order to extend the monitoring strategy, 10,000 L (10 Nm³) of krypton (Kr) were injected as an additional conservative chemical tracer. Moreover, CO₂ from a natural CO₂ source was injected instead of the previously used industrial CO₂ from a refinery process. The natural CO₂ has a much heavier carbon isotope composition ($\delta^{13}C = -3.4 \pm 0.2\%$) compared to the industrial CO₂ ($\delta^{13}C = -30.6 \pm 0.4\%$) and additionally allows for examination of isotopic effects due to mixing between the injected natural CO₂ and formation brine, and previously injected industrial CO₂. Vital parameters during monitoring include injection rates of N₂ and CO₂, pressure and temperature at the injection and observation wells, and reservoir pressure, respectively. A permanently installed capillary riser tube was used for collecting reservoir fluid and gas samples. These were analyzed for gas and carbon isotope compositions.

Preliminary results show the successful realization of the N₂-CO₂ co-injection field test next to effective and permanent monitoring of the injected gases (N₂, CO₂ and Kr). During the field test, 32 t of N₂ and 613 t of CO₂ were co-injected in total to ensure a CO₂:N₂ volume ratio of approximately 95:5. Despite some variation of both N₂ and CO₂ injection rates, wellhead pressure and reservoir pressure were well controlled during the entire field test, and thereafter. Based on Kr data determined by mass spectrometry measurements, the gas mixture arrived after about 4 days at the first observation well (Ktzi 203) located about 20 m away from the injection well (Ktzi 201).

Increasing Kr concentrations at the Ktzi 203 observation well positively correlate with both increasing N₂ concentrations as well as δ^{13} C values. Additionally, the δ^{13} C data also indicate mixing between natural and industrial CO₂ within the reservoir.