




Geomechanical Risk Assessment Using Field Scale Geomechanics 3D Model: Case Study on Smeaheia CO₂ Storage Site

18.June.2019

Jung Chan CHOI, Huynh Dat Vu Khoa, Elin Skurtveit, Lars Grande, Joonsang Park




Smeaheia CO2 storage site



- Located at Horda Platform East of Troll field
- High porous saline aquifer reservoir at the depth of 1200-1500 m below sea level
- Two large storage structures Alpha and Beta, which has CO2 storage capacity of 100 Mt each


Geomechanics risk on Smeaheia



- ↪ Reactivation of Vette and Øygarden faults
- ↪ Caprock integrity
- ↪ Seabed heave and Associated geohazard


Previous study on derisking CO2 storage sites

Fault stability for Smeaheia area



Skurtveit et al., 2018


2D geomechanics model for Snøhvit



Choi et al., 2015




Objective and scope of work

- Aims to develop full 3D FE model for geomechanical stability analyses of reservoir at Smeaheia site
- improving understanding on the stress change and associated instability in caprock and faults in Smeaheia site



Modeling procedure

➤ NGI's in-house workflow that can build 3D geomechanics model by linking Eclipse, Geomechanics and Abaqus is used





Geometry

- ↗ 9 Fm. or Gp. are included
- ↗ Number elements = 1.5 mil
- ↗ Element type: C3D8RP (8-node trilinear displacement and pore pressure, reduced integration)

Reservoir


Layer No.	Top of layer	Depth_mean	thickness
100	Seabed.txt	-301.5	513.8
201	Top Shetland Gp.txt	-815.3	255.86
302	Draupne Fm.txt	-1071.16	204.24
403	Sognefjord Fm.txt	-1275.4	162.1
504	Fensfjord Fm.txt	-1437.5	125.7
605	Brent Gp.txt	-1563.2	13.5
706	Dunlin Gp.txt	-1576.7	22.1
807	Johansen Fm.txt	-1598.8	25.5
908	Top Statfjord Fm.txt	-1624.3	1375.7
	Bottom of the model	-3000	



Stress condition



➤ Data from Northern Lights data package

- $K_0 = 0.45$
- $\text{Gamma}_{v_eff} = 10.235 \text{ kPa/m}$ from seabed
- $\text{Hydrostatic}_{pp_gradient} = 9.905 - 10.069 \text{ kPa/m}$



Material input

- Data package from Northern Lights project and internal NGI database are used.
- Porosity dependent material properties are used for the reservoir



Reservoir pressure

- Reservoir simulation from Equinor 2016 feasibility study (Statoil, 2016) are used as a basis.
- Injection of 1.3 MT CO₂/yr during 25yrs (total injection of 32.MT CO₂) is considered for the model.
- The injection well is considered as SDL#2, which is in Alpha structure.
- At 2045, the pressure build up near injector is around 11 bar








Figure 9-1: Porosity map and location of three proposed well locations for Smeethela reservoir.

Pressure build-up in the reservoir





Vertical deformation in reservoir



Yr 2045

Unit: m




Yr 2145





Seabed heave

Maximum seabed heave is less than 5cm. Low risk on seabed geohazard





Unit: m




Injection-induced porosity change in the reservoir

➤ Porosity change is less than 0.1% during the injection




Stress path in reservoir

Failure during the planned injection is unlikely




Vertical effective stress Yr2045




Stress change and integrity in the caprock

- Maximum stress change in the caprock is about 200 kPa (<20% max change in reservoir).
- Mechanical failure of caprock is unlikely for the selected injection scenario

Change in vertical effective stress Yr2045




— Draupne Shale: $c = 7.0 \text{ MPa}$, $\phi = 13.0^\circ$
— Cohesionless: $c = 0.0 \text{ MPa}$, $\phi = 31.0^\circ$



Stability of Vette fault

- In the given scenario, reactivation of Vette fault is unlikely.
- The analytical approach used in Skurtveit et al., (2018) seems to be conservative



Summary

- This study presents how to evaluate the geomechanical risk of CO₂ storage using a field scale 3D geomechanics model.
- For Smeaheia area, when the injection of 1.3 MT CO₂/yr during 25yrs at the SDL#2 is considered, the evaluated geomechanical risks are as follows:
 - Seabed heave and associated geohazard: Low
 - Injection-induced caprock integrity: Low
 - Injection-induced porosity change in reservoir: <1%
 - Reactivation of Vette fault: Low
- 3D geomechanics model is ready to investigate effects of various scenario easily. Further works incorporated with other research projects (SPHINCCS, OASIS, NCCS, IGCCS) are ongoing to investigate various scenarios (e.g. different injection scenario, effect of depletion in Troll, microseismicity, etc..)

Thank you for your attention!

This publication has been produced with support from the NCCS Centre, performed under the Norwegian research program Centres for Environment-friendly Energy Research (FME). The authors acknowledge the following partners for their contributions: Aker Solutions, Ansaldo Energia, CoorsTek Membrane Sciences, Emgs, Equinor, Gassco, Krohne, Larvik Shipping, Norcem, Norwegian Oil and Gas, Quad Geometrics, Shell, Total, Vår Energi, and the Research Council of Norway.

Work was conducted in close collaboration with the Northern Lights project (Equinor, Total, Shell).





#onsafeground

